

Unix timestamp (seconds)

10-digit Unix epoch in seconds.

```
^\d{10}$
```

Token-by-token breakdown

Token	Meaning
^	start of string (or line in multiline mode)
\d{10}	exactly 10 times: digit (0–9)
\$	end of string (or line in multiline mode)

Quick usage in 7 languages

JavaScript	<pre>const re = /^\d{10}\$/; re.test(value);</pre>
Python	<pre>import re re.match(r"^\d{10}\$", value)</pre>
Java	<pre>Pattern.compile("^\d{10}\$").matcher(value).matches();</pre>
C# / .NET	<pre>Regex.IsMatch(value, @"^\d{10}\$");</pre>
Go	<pre>regexp.MustCompile(`^\d{10}\$`).MatchString(value)</pre>
Ruby	<pre>/^\d{10}\$/ .match?(value)</pre>
PHP	<pre>preg_match('~^\d{10}\$~', \$value);</pre>

Common pitfalls

- **Anchored to the whole string.** This pattern uses ^ and \$, so it requires the entire input to match. To find it inside a longer text, drop the anchors and use the global (g) flag.
- **Escape it correctly per language.** In Java and JavaScript strings each backslash must be doubled (\d); in Python, Go, and C# use raw/verbatim strings so the backslashes survive.
- **Validate beyond format.** Matching the format doesn't guarantee the value is real. Confirm the unix timestamp (seconds) against a source of truth (database, API, or checksum) where it matters.